



L型三爪联轴器 L three-claw coupling

产品结构：由两个烧结合金或铝合金凸补件加一个NBR橡胶垫组成。

配轴径：9mm-75mm

产品特点：●能有效吸收动力冲击；




- 安全方便、简单、成本低、骨绩小；
- 耐高温、同油性佳、免保养；
- 最大持力达54.2kg-m；
- 容许偏差：径向偏差：0.3mm
- 角度偏心：1°，轴向偏差：+0.5mm

Product structure: consists of two sintered alloys or aluminum alloy convex parts and a NBR rubber

Axial diameter: 9mm-75mm

Product features: ●Effective absorption;

- Safe and convenient, simple, low cost and small bone perfor;
- High temperature resistance, good oil property and no maintenance;
- The maximum holding force 54.2kg-m;
- Admissible deviation: Radial deviation: 0.3mm
- Angle eccentricity: 1°, Axial deviation: +0.5mm



产品型号 Product model	常用扭力kg-m Common torsion kg-m	标准孔径 Standard aperture	最高转速 rpm Maximum speed rpm	最大孔径 Maximum aperture	A	B	C	D	E	重量kg Weight kg
L035	0.05	—	30000	9	16	21	8	6.5	—	0.03
L050	0.3	Φ11Φ14	17000	16	27.4	43	12	15.5	—	0.13
L070	0.5	Φ11Φ14Φ19	10000	19	35	51	13	19	—	0.24
L075	1	Φ11Φ14Φ19	9000	24	45	54	13	20.5	—	0.4
L090	1.6	Φ14Φ19Φ24	9000	25	54	55	13	21	—	0.68
L095	2.2	14 19 24 28	7000	28	54	64	13	25.5	—	0.71
L100	5.0	Φ19Φ24Φ28Φ32	5000	38	66	89	19	35	—	1.4
L110	9.0	Φ24Φ28Φ32Φ38Φ42	5000	42	84	108	22	43	—	3
L150	15.0	Φ28Φ32Φ42Φ48	5000	48	96	115	25	45	80	5.02
L190	20.0	—	5000	55	115	124	25	54	102	7.6
L225	30.0	—	4200	65	127	154	26	64	108	9
L275	54.2	—	4200	75	157	200	41	79	127	21