



摩托车传动链
MOTORCYCLE
DRIVE CHAIN

Standard

GL 链号 Chain No.	节距 Pitch	类型 Bush Type	宽度 Width	销轴直径 Pin diameter	销轴长度 Pin length	滚子直径 Roller diameter	链板厚度 Plate Thickness		拉伸 Tensile	重量 Weight
							内 Linner	外 Outer		
	mm		mm	mm	mm	mm	mm	mm	KN	Kg/m
420	12.700	Curled	6.35	3.96	14.7	7.77	1.50	1.50	18.1	0.55
428	12.700	Curled	7.75	4.45	16.5	8.51	1.50	1.50	20.1	0.71
520	15.875	Curled	6.35	5.08	17.5	10.14	2.03	2.03	29.9	0.89
525	15.875	Curled	7.94	5.08	19.4	10.14	2.03	2.03	29.9	0.93
530	15.875	Curled	9.53	5.08	20.7	10.14	2.03	2.03	29.9	1.09
630	19.050	Curled	9.50	5.94	22.7	11.91	2.40	2.40	38.1	1.50

Reinforced

常规标准型和加强型摩链是中链的经济型摩托车链条。标准型和加强型链条采用的是有缝小管，主要用于普通公路摩托车及正常道路上行驶的摩托车。

外片颜色主要有:本色, 喷丸, 发蓝, 发黄。

Standard&Reinforce are economic motorcycle chain lines. With curled bushing. Standard&Reinforce Chains are redesigned for low performance motorcycles with medium and low capacity up to 250CC and mopeds. Outer plate color available: Steel Natural Color; Black Finished; Blue Finished; Yellow Finished.

GL 链号 Chain No.	节距 Pitch	类型 Bush Type	宽度 Width	销轴直径 Pin diameter	销轴长度 Pin length	滚子直径 Roller diameter	链板厚度 Plate Thickness		拉伸 Tensile	重量 Weight
							内 Linner	外 Outer		
	mm		mm	mm	mm	mm	mm	mm	KN	Kg/m
415H	12.700	Curled	4.76	3.96	13.00	7.76	1.50	1.50	17.9	0.59
420H	12.700	Curled	6.35	3.96	16.00	7.77	1.85	1.85	20.0	0.69
428H	12.700	Curled	7.94	4.45	18.50	8.51	1.85	1.85	23.5	0.89
428H	12.700	Curled	7.94	4.45	18.80	8.51	2.00	2.00	24.5	0.96
520H	15.875	Curled	6.35	5.08	19.10	10.14	2.35	2.35	29.9	0.96
525H	15.875	Curled	7.94	5.08	20.90	10.14	2.35	2.35	29.9	1.00
530H	15.875	Curled	9.53	5.08	22.10	10.14	2.35	2.35	29.9	1.15

O-Ring

油封链O-Ring型链条实现了销轴和小管永久的润滑密封, 这也保证了链条更长的使用寿命和最小的磨损. 采用了无缝小管, 高质量的销轴原料和四边铆头设计, 标准型O型圈链条和加强型O型圈链条。但是主推的是加强型O型圈链条, 因为它的使用范围更加广阔。

链片颜色有: 红色, 黄色, 橙色, 绿色, 蓝色

O-Ring Chains achieve permanent Lubrication Sealing between pin & bush which ensure with longer lifetime and minimum maintenance. With Solid Bushing, High Quality of Pin Material and 4-side riveting, with both standard & reinforced O-Ring chains. But recommend reinforced O-Ring chains since it has even better performance which covers almost all the range of motorcycles.

Outer Plate Color Available: Copper, nickel,

Painted Color Plate Available: Red, Yellow, Orange, Green, Blue

GL 链号 Chain No.	节距 Pitch	类型 Bush Type	宽度 Width	销轴直径 Pin diameter	销轴长度 Pin length	滚子直径 Roller diameter	链板厚度 Plate Thickness		拉伸 Tensile	重量 Weight
							内 Linner	外 Outer		
	mm		mm	mm	mm	mm	mm	mm	KN	Kg/m
520-O	15.875	Solid	6.35	5.24	20.6	10.16	2.03	2.03	30.4	0.94
525-O	15.875	Solid	7.94	5.24	22.5	10.16	2.03	2.03	30.4	0.98
530-O	15.875	Solid	9.50	5.24	23.8	10.16	2.03	2.03	30.4	1.11
428H-O	12.700	Solid	7.94	4.45	21.6	8.51	2.00	2.00	23.8	0.98
520H-O	15.875	Solid	6.35	5.24	22.0	10.16	2.35	2.35	34.0	1.00
525H-O	15.875	Solid	7.94	5.24	23.8	10.16	2.35	2.35	34.0	1.12
530H-O	15.875	Solid	9.60	5.24	25.4	10.16	2.35	2.35	34.0	1.20

X-Ring

油封链X-Ring型链条实现了销轴和小管永久的润滑密封, 这也保证了链条更长的使用寿命和最小的磨损. 采用了无缝小管, 高质量的销轴原料和四边铆头设计, 标准型X型圈链条和加强型X型圈链条。但是主推的是加强型X型圈链条, 因为它的使用范围更加广阔。

链片颜色有: 红色, 黄色, 橙色, 绿色, 蓝色

X-Ring Chains achieve permanent Lubrication Sealing between pin & bush which ensure with longer lifetime and minimum maintenance. With Solid Bushing, High Quality of Pin Material and 4-side riveting, with both standard & reinforced X-Ring chains. But recommend reinforced X-Ring chains since it has even better performance which covers almost all the range of motorcycles.

Outer Plate Color Available: Copper, nickel,

Painted Color Plate Available: Red, Yellow, Orange, Green, Blue

GL 链号 Chain No.	节距 Pitch	类型 Bush Type	宽度 Width	销轴直径 Pin diameter	销轴长度 Pin length	滚子直径 Roller diameter	链板厚度 Plate Thickness		拉伸 Tensile	重量 Weight
							内 Linner	外 Outer		
	mm		mm	mm	mm	mm	mm	mm	KN	Kg/m
520-X	15.875	Solid	6.35	5.24	20.6	10.16	2.03	2.03	30.4	0.94
525-X	15.875	Solid	7.94	5.24	22.5	10.16	2.03	2.03	30.4	0.98
530-X	15.875	Solid	9.50	5.24	23.8	10.16	2.03	2.03	30.4	1.11
428H-X	12.700	Solid	7.94	4.45	21.6	8.51	2.00	2.00	23.8	0.98
520H-X	15.875	Solid	6.35	5.24	22.0	10.16	2.35	2.35	34.0	1.00
525H-X	15.875	Solid	7.94	5.24	23.8	10.16	2.35	2.35	34.0	1.12
530H-X	15.875	Solid	9.60	5.24	25.4	10.16	2.35	2.35	34.0	1.20

