


## NL型齿式弹性联轴器 NL type toothed elastic coupling

- ●使用简单,易维修,缓冲吸振;
- ●可补偿较大的轴向位移,微量的径向位移和角位移;
- ●适用于正反向变化多,启动频繁的高速轴。
- Easy to use, easy to repair, buffer vibration;
- Compensable large axial displacement, micro radial displacement and angular displace;
- It is suitable to change many reverse changes and start the high speed shaft.





型号Model	DH	LH	D	d1, d2最大值 Maximum value	III, I2最大值 Maximum value	Е	K	边数 The number of teeth	摸数 Modulus	透用电机功率最大值(KW) Masimum power of motor (KW)	公称扭矩N.m Nominal torque N.n
NL1	40	40	26	16	25	5	27	20	1.5	0.75	40
NLT	40	40	26	16	25	5	21	32	1	0.75	40
NL2	57	35	36	24	50	6	39	28	1.5	1.1	100
IVLZ	37	33	30	24	50	0	39	48	1	1.1	100
NL3	68	45	47	28	60	6	46	25	2	4	160
INLO	00	43	. 4.7	20	00	0	40	34	1.5		100
NL4	82	47	58	38	80	8	61	32	2	7.5	250
IVL4	02	47	56	30	00	0	01	45	1.5		250
NL5	93	50	68	42	110	10	70	36	2	15	315
IVES	33	50	00	42	110	10	70	38	2	15	313
								40	2		
NL6	102	52	70	48	110	12	77	32	2.5	22	400
								41	2		
								36	2.5		
NL7	116	60	80	55	110	11	84	42	2	30	630
								45	2		
								36	3		
NL8	140	72	96	65	140	11	101	42	2.5	- 55	1250
IVLO	140	12	30	0.5	140	1.1.	101	45	2.5	55	1230
								31	3		
大NL9	175	93	124	80	170	16	129	45	3	90	2000
701123			124	30			120	46	3	30	2000
NL10	220	80	157	95	170	19	167	44	4	180	3150
订货描述 Order description			名称Name		型号Model			内孔中d1*轴孔长I1/内孔中d2*轴孔长I2 The inner hole od1*Axial length II/The inner hole od1*Axial length			
				联轴器	Coupling		ML3			Ф25*40Ф28	8*60

## NL型齿式联轴器尼龙齿套 NL tooth coupling nylon sleeve

NL联轴器是目前国内的最新产品,在国内外已经广泛地被采用,该产品由机械委济南铸造锻压机械 研究所设计,适用于轴间及挠性传动,允许较大的轴向径向位移和角位移,并具有结构简单、维修方便、 拆装容易、噪声低、传动功效损失小、使用寿命长等优点,倍受用户欢迎。

为满足各种机械的更新改选及引进设备备件需要,我厂可以提供品种规格齐全的内齿形弹性联轴器, 并且根据用户需要接受非标准订货。

NL coupling is the latest product in China. It has been widely used at home and abroad.

The product is designed by the Ji'nan Institute of foundry and forging machinery, and is suitable for inter axie and flexible transmission. It allows larger axial radial displacement and angular displacement, and has the advantages of simple structure, convenient maintenance, easy disassembly and assembly, low noise, little loss of transmission efficiency and long service life. It is welcomed by users.

In order to meet all kinds of mechanical renewal and selection and equipment spare parts, our factory can provide all kinds of internal tooth elastic couplings with various specifications, and accept non-standard orders according to users' needs.



## NL型齿式联轴器尼龙齿套产品目录 NL tooth coupling nylon sleeve product catalogue

名称 Name	型号Model	齿数The number of teeth	摸数Modulus
尼龙套 Nylon jacket	NL1	32/30齿	1/1.5
尼龙套 Nylon jacket	NL2	42/28齿	1/1.5
尼龙套 Nylon jacket	NL3	25/34齿	2/1.5
尼龙套 Nylon jacket	NL4	32/45齿	2/1.5
尼龙套 Nylon jacket	NL5	36/38齿	2
尼龙套 Nylon jacket	NL6	32/40齿	2.5/2
尼龙套 Nylon jacket	NL7	45/36齿	2/2.5
尼龙套 Nylon jacket	NL8	31/36/42/45齿	3/2.5
尼龙套 Nylon jacket	NL9	45/46齿	3
尼龙套 Nylon jacket	NL10	44齿	4

11