



PLATEWEELS


K 25A

K 25A

SPROCKETS mm  
Tooth width (T) 2.8

CHAIN mm  
Pitch (P) 6.35  
Internal width 3.18  
Roller  $\Phi$  (Dr) 3.30

Type	Teeth	Do	Dp	Bore d		Wt kg	Material
				Stock	Min		
K 25A	10	23	20.55	9	11	0.02	C45 Solid
	12	28	24.53	9	11	0.03	
	13	30	26.53	9	11	0.04	
	14	32	28.54	9	11	0.04	
	15	34	30.54	9	11	0.05	
	16	36	32.55	9	11	0.05	
	17	38	34.56	9	11	0.07	
	18	40	36.57	9	11	0.07	
	20	44	40.59	9	11	0.09	
	24	52	48.65	9	11	0.14	
	25	54	50.66	9	11	0.16	
	27	58	54.70	9	11	0.17	
	28	60	56.71	9	11	0.18	
	29	62	58.73	9	11	0.20	
	30	64	60.75	10	12	0.23	
	32	68	64.78	10	12	0.27	
	33	70	66.80	10	12	0.28	
	35	74	70.84	10	12	0.30	
	36	76	72.86	10	12	0.32	
	37	78	74.88	10	12	0.37	
	38	80	76.90	10	12	0.41	
	40	84	80.93	11	13	0.43	
	42	89	84.97	11	13	0.47	
	45	95	91.03	11	13	0.50	
	50	105	101.13	11	13	0.59	
	55	115	111.23	11	13	0.70	
	60	125	121.33	11	13	0.87	
	70	145	141.54	11	13	1.81	
	75	155	151.64	12	14	1.37	
	80	165	161.74	12	14	1.62	



PLATEWEELS


K 35A

K 35A

SPROCKETS mm  
Tooth width (T) 4.3

CHAIN mm  
Pitch (P) 9.525  
Internal width 4.78  
Roller  $\Phi$  (Dr) 5.08

Type	Teeth	Do	Dp	Bore d		Wt kg	Material
				Stock	Min		
K 35A	10	34	30.02	9	11	0.02	C45 Solid
	11	38	33.01	9	11	0.03	
	12	41	36.00	9	11	0.03	
	13	44	39.00	9	11	0.04	
	14	47	42.01	9	11	0.04	
	15	51	45.01	9	11	0.05	
	16	54	48.02	9	11	0.05	
	17	57	51.04	11	13	0.07	
	18	60	54.05	11	13	0.07	
	19	63	57.07	11	13	0.09	
	20	66	60.09	11	13	0.09	
	21	69	63.11	11	13	0.11	
	22	72	66.13	11	13	0.11	
	23	75	69.15	11	13	0.11	
	24	78	72.17	11	13	0.14	
	25	81	75.19	11	13	0.16	
	26	84	78.21	11	13	0.16	
	27	87	81.23	11	13	0.17	
	28	90	84.25	11	13	0.18	
	30	96	91.27	11	13	0.23	
	32	102	97.29	11	13	0.27	
	33	105	100.31	11	13	0.28	
	34	109	103.33	11	13	0.29	
	35	112	106.35	11	13	0.30	
	36	115	109.37	12	14	0.32	
	38	121	115.39	12	14	0.37	
	40	127	121.41	12	14	0.40	
	42	133	127.43	16	18	0.43	
	45	142	136.45	16	18	0.49	
	46	145	139.47	16	18	0.51	
	48	151	145.49	16	18	0.55	
	50	157	151.51	16	18	0.60	
54	169	163.53	16	18	0.70		
55	172	166.55	16	18	0.71		
60	187	182.57	16	18	0.80		
65	203	197.59	16	18	1.02		
70	218	212.61	16	18	1.18		
80	248	242.63	16	18	1.50		






### PLATEWEELS

### K 410A

Type	Teeth	Do	Dp	Bore d		Wt kg	Material
				Stock	Min		
K 410A	8	30	33.19	10	12	0.01	C45 Solid
	9	42	37.13	10	12	0.02	
	10	46	41.10	11	13	0.05	
	11	51	45.08	12	14	0.09	
	12	55	49.07	12	14	0.10	
	13	59	53.07	15	17	0.12	
	14	63	57.07	15	17	0.14	
	15	67	61.08	15	17	0.16	
	16	71	65.10	15	17	0.18	
	17	76	69.12	15	17	0.20	
	18	80	73.14	15	17	0.23	
	19	84	77.16	15	17	0.26	
	20	88	81.18	16	18	0.29	
	21	92	85.21	16	18	0.30	
	22	96	89.24	16	18	0.35	
	23	100	93.27	16	18	0.38	
	24	104	97.30	16	18	0.40	
	25	108	101.33	16	18	0.45	
	26	112	105.36	16	18	0.49	
	27	116	109.40	16	18	0.50	
	28	120	113.43	16	18	0.56	
	29	124	117.46	16	18	0.60	
	30	128	121.50	16	18	0.63	
	31	133	125.53	16	18	0.65	
	32	137	129.57	16	18	0.70	
	33	141	133.61	16	18	0.75	
	34	145	137.64	16	18	0.80	
	35	149	141.68	16	18	0.85	
	36	153	145.72	18	20	0.90	
	37	157	149.75	18	20	0.99	
	38	161	153.79	18	20	1.00	
	39	165	157.83	18	20	1.18	
	40	169	161.87	18	20	1.20	
	41	173	165.91	18	20	1.20	
	42	177	169.94	18	20	1.25	
	44	185	178.02	18	20	1.35	
	45	189	182.06	18	20	1.40	
	46	193	186.10	18	20	1.49	
	47	197	190.14	18	20	1.58	
	48	201	194.18	18	20	1.63	
	49	205	198.22	18	20	1.73	
	50	209	202.26	18	20	1.80	
	52	218	210.34	18	20	1.93	
	54	226	218.42	18	20	2.00	
	60	250	242.66	18	20	2.60	

**K 410A**  
 SPROCKETS mm  
 Tooth width (T) 2.8  
 CHAIN mm  
 Pitch (P) 12.70  
 Internal width 3.40  
 Roller Ø(Dr) 7.75



### PLATEWEELS

### K 40A

Type	Teeth	Do	Dp	Bore d		Wt kg	Material
				Stock	Min		
K 40A	10	46	41.10	9.5	11.5	0.05	C45 Solid
	11	51	45.08	10.5	12.5	0.09	
	12	55	49.07	11.5	13.5	0.10	
	13	59	53.07	13.5	15.5	0.12	
	14	63	57.07	13.5	15.5	0.14	
	15	67	61.08	13.5	15.5	0.16	
	16	71	65.10	13.5	15.5	0.18	
	17	76	69.12	13.5	15.5	0.20	
	18	80	73.14	13.5	15.5	0.23	
	19	84	77.16	13.5	15.5	0.26	
	20	88	81.18	14	16	0.29	
	21	92	85.21	14	16	0.30	
	22	96	89.24	14	16	0.35	
	23	100	93.27	14	16	0.38	
	24	104	97.30	14	16	0.40	
	25	108	101.33	14	16	0.45	
	26	112	105.36	14	16	0.49	
	27	116	109.40	14	16	0.50	
	28	120	113.43	14	16	0.56	
	29	124	117.46	14	16	0.60	
	30	128	121.50	14	16	0.63	
	31	133	125.53	14	16	0.65	
	32	137	129.57	14	16	0.70	
	33	141	133.61	14	16	0.75	
	34	145	137.64	14	16	0.80	
	35	149	141.68	14	16	0.85	
	36	153	145.72	16	18	0.90	
	37	157	149.75	16	18	0.99	
	38	161	153.79	16	18	1.00	
	39	165	157.83	16	18	1.15	
	40	169	161.87	16	18	1.20	
	41	173	165.91	16	18	1.20	
	42	177	169.94	16	18	1.25	
	43	181	173.98	16	18	1.30	
	44	185	178.02	16	18	1.35	
	45	189	182.06	16	18	1.40	
	46	193	186.10	16	18	1.49	
	47	197	190.14	16	18	1.58	
	48	201	194.18	16	18	1.63	
	49	205	198.22	16	18	1.73	
	50	209	202.26	16	18	1.80	
	51	214	206.30	16	18	1.88	
	52	218	210.34	16	18	1.93	
	53	222	214.38	16	18	1.98	
	54	226	218.42	16	18	2.00	
	55	230	222.46	16	18	2.18	
	56	234	226.50	16	18	2.26	
	58	242	234.58	16	18	2.43	
	59	246	238.62	16	18	2.51	
	60	250	242.66	16	18	2.60	
	62	258	250.74	16	18	2.77	
	64	266	258.83	16	18	2.90	
	65	270	262.87	16	18	3.00	
	68	282	274.99	16	18	3.35	
	70	290	283.07	16	18	3.50	
	72	299	291.16	20	22	3.70	
	75	311	303.28	20	22	4.00	
	80	331	323.49	20	22	4.60	
	85	351	343.69	20	22	5.20	
	90	371	363.90	20	22	5.80	

**K 40A**  
 SPROCKETS mm  
 Tooth width (T) 7.2  
 CHAIN mm  
 Pitch (P) 12.7  
 Internal width 7.95  
 Roller Ø(Dr) 7.95






### PLATEWEELS

### K 50A

Type	Teeth	Do	Dp	Bore d		Wt kg	Material
				Stock	Min		
K 50A	10	58	51.37	14	16	0.14	C45 Solid
	11	64	56.35	14	16	0.17	
	12	69	61.34	14	16	0.20	
	13	74	66.34	14	16	0.23	
	14	79	71.34	14	16	0.27	
	15	84	76.35	14	16	0.30	
	16	89	81.37	14	16	0.35	
	17	94	86.39	14	16	0.40	
	18	100	91.42	14	16	0.45	
	19	105	96.45	14	16	0.48	
	20	110	101.48	14	16	0.50	
	21	115	106.51	14	16	0.60	
	22	120	111.55	16	18	0.66	
	23	125	116.58	16	18	0.72	
	24	130	121.62	16	18	0.78	
	25	135	126.66	16	18	0.85	
	26	140	131.70	16	18	0.90	
	27	145	136.74	16	18	1.00	
	28	150	141.79	16	18	1.05	
	29	155	146.83	16	18	1.12	
	30	161	151.87	16	18	1.20	
	31	166	156.92	16	18	1.30	
	32	171	161.96	16	18	1.35	
	33	176	167.01	16	18	1.45	
	34	181	172.05	16	18	1.55	
	35	186	177.10	16	18	1.65	
	36	191	182.14	16	18	1.75	
	37	196	187.19	16	18	1.85	
	38	201	192.24	16	18	1.95	
	39	206	197.29	16	18	2.05	
	40	211	202.33	16	18	2.15	
	41	216	207.38	16	18	2.25	
	42	221	212.43	16	18	2.40	
	43	226	217.48	16	18	2.50	
	44	231	222.53	16	18	2.60	
	45	237	227.58	16	18	2.70	
	46	242	232.63	16	18	2.88	
	47	247	237.68	16	18	3.01	
	48	252	242.73	16	18	3.10	
	49	257	247.78	16	18	3.27	
50	262	252.83	16	18	3.40		
51	267	257.88	16	18	3.55		
52	272	262.92	16	18	3.69		
53	277	267.97	16	18	3.83		
54	282	273.02	16	18	3.95		
55	287	278.08	16	18	4.13		
56	292	283.13	16	18	4.28		
57	297	288.18	16	18	4.44		
58	302	293.23	16	18	4.59		
59	307	298.28	16	18	4.75		
60	312	303.33	16	18	4.90		
64	333	323.53	20	22	5.60		
65	338	328.58	20	22	5.75		
68	353	343.74	20	22	6.32		
70	363	353.84	20	22	6.70		
72	373	363.94	20	22	7.05		
75	388	379.10	20	22	7.70		
80	414	404.36	20	22	8.70		
90	464	454.88	20	22	11.00		

**K 50A**  
 SPROCKETS mm  
 Tooth width (T) 8.7  
 CHAIN mm  
 Pitch (P) 15.875  
 Internal width 9.53  
 Roller Φ(Dr) 10.16




### PLATEWEELS

### K 60A

Type	Teeth	Do	Dp	Bore d		Wt kg	Material
				Stock	Min		
K 60A	10	68	61.65	14	16	0.27	C45 Solid
	11	76	67.62	14	16	0.30	
	12	85	73.60	14	16	0.38	
	13	89	79.60	14	16	0.45	
	14	95	85.61	16	18	0.50	
	15	101	91.62	16	18	0.60	
	16	107	97.65	16	18	0.65	
	17	113	103.67	16	18	0.75	
	18	119	109.71	16	18	0.84	
	19	126	115.74	16	18	0.93	
	20	132	121.79	16	18	1.05	
	21	138	127.82	16	18	1.15	
	22	144	133.86	16	18	1.25	
	23	150	139.90	16	18	1.40	
	24	156	145.95	16	18	1.50	
	25	162	151.99	16	18	1.62	
	26	168	158.04	16	18	1.78	
	27	174	164.09	20	22	1.90	
	28	180	170.14	20	22	2.05	
	29	187	176.20	20	22	2.20	
	30	193	182.25	20	22	2.35	
	31	199	188.30	20	22	2.50	
	32	205	194.35	20	22	2.68	
	33	211	200.41	20	22	2.85	
	34	217	206.46	20	22	3.02	
	35	223	212.52	20	22	3.25	
	36	229	218.57	20	22	3.40	
	37	235	224.63	20	22	3.60	
	38	241	230.69	20	22	3.80	
	39	247	236.74	20	22	4.00	
	40	253	242.80	20	22	4.20	
	41	260	248.86	20	22	4.45	
	42	266	254.92	20	22	4.63	
	43	272	260.98	20	22	4.85	
	44	278	267.03	20	22	5.10	
	45	284	273.09	20	22	5.30	
	46	290	279.15	20	22	5.59	
	47	296	285.21	20	22	5.83	
	48	302	291.27	20	22	6.10	
	49	308	297.33	20	22	6.34	
50	314	303.39	20	22	6.60		
51	320	309.45	20	22	6.87		
52	326	315.51	20	22	7.15		
54	338	327.63	20	22	7.70		
55	345	333.69	20	22	8.00		
57	357	345.81	20	22	8.59		
58	363	351.87	20	22	8.90		
60	375	363.99	20	22	9.50		
65	405	394.30	26	28	11.20		
70	436	424.61	26	28	13.00		
72	448	436.73	26	28	13.70		
75	466	454.92	26	28	14.90		
80	496	485.23	26	28	16.90		
90	557	545.85	26	28	21.40		

**K 60A**  
 SPROCKETS mm  
 Tooth width (T) 11.7  
 CHAIN mm  
 Pitch (P) 19.05  
 Internal width 12.70  
 Roller Φ(Dr) 11.91





PLATEWEELS


K 80A

Type	Teeth	Do	Dp	Bore d		Wt kg	Material
				Stock	Min		
K 80A	10	93	82.19	16	18	0.60	C45 S&B
	11	102	90.16	16	18	0.73	
	12	110	98.14	16	18	0.83	
	13	118	106.14	16	18	1.00	
	14	127	114.15	16	18	1.16	
	15	135	122.17	20	22	1.30	
	16	143	130.20	20	22	1.50	
	17	151	138.23	20	22	1.70	
	18	159	146.27	20	22	1.90	
	19	167	154.32	20	22	2.10	
	20	176	162.37	20	22	2.35	
	21	184	170.42	20	22	2.57	
	22	192	178.48	26	28	2.82	
	23	200	186.54	26	28	3.10	
	24	208	194.60	26	28	3.35	
	25	216	202.66	26	28	3.65	
	26	224	210.72	26	28	3.95	
	27	233	218.79	26	28	4.25	
	28	241	226.86	26	28	4.60	
	29	249	234.93	26	28	4.93	
	30	257	243.00	26	28	5.30	
	31	265	251.07	26	28	5.63	
	32	273	259.14	26	28	6.00	
	33	281	267.21	26	28	6.40	
	34	289	275.29	26	28	6.80	
	35	297	283.36	26	28	7.20	
	36	306	291.43	26	28	7.60	
	37	314	299.51	26	28	8.00	
	38	322	307.58	26	28	8.50	
	39	330	315.66	26	28	8.90	
	40	338	323.74	26	28	9.40	
	41	346	331.81	26	28	9.90	
	42	354	339.89	26	28	10.30	
	43	362	347.97	26	28	10.80	
	44	370	356.04	26	28	11.40	
	45	378	364.12	26	28	11.90	
	46	387	372.20	26	28	12.40	
	47	395	380.28	26	28	12.95	
	48	403	388.36	26	28	13.50	
	49	411	396.44	26	28	14.08	
	50	419	404.52	26	28	14.70	
	52	435	420.68	26	28	15.86	
	53	443	428.76	26	28	16.48	
	54	451	436.84	26	28	17.10	
	55	459	444.92	26	28	17.75	
	56	468	453.00	26	28	18.40	
	57	476	461.08	26	28	19.07	
	58	484	469.16	26	28	19.75	
	60	500	485.33	26	28	21.10	
	64	532	517.65	26	28	24.05	
	65	540	525.73	26	28	24.80	
	66	548	533.82	26	28	25.58	
	70	581	566.15	26	28	28.80	
	75	621	606.56	26	28	33.10	
	80	662	646.97	26	28	37.60	
	90	743	727.80	26	28	47.60	

K 80A

SPROCKETS mm  
Tooth width (T) 14.6

CHAIN mm  
Pitch (P) 25.4  
Internal width 15.88  
Roller  $\phi$ (Dr) 15.88



PLATEWEELS


K 100A

Type	Teeth	Do	Dp	Bore d		Wt kg	Material
				Stock	Min		
K 100A	10	117	102.74	20	22	1.10	C45 Solid
	11	127	112.70	20	22	1.30	
	12	138	122.67	20	22	1.60	
	13	148	132.67	20	22	1.90	
	14	158	142.68	20	22	2.15	
	15	168	152.71	20	22	2.50	
	16	179	162.74	20	22	2.83	
	17	189	172.79	20	22	3.20	
	18	199	182.84	20	22	3.60	
	19	209	192.90	20	22	4.00	
	20	220	202.96	20	22	4.40	
	21	230	213.03	20	22	4.90	
	22	240	223.10	20	22	5.35	
	23	250	233.17	20	22	5.80	
	24	260	243.25	20	22	6.40	
	25	270	253.32	20	22	6.90	
	26	281	263.40	20	22	7.50	
	27	291	273.49	20	22	8.10	
	28	301	283.57	20	22	8.70	
	29	311	293.66	20	22	9.30	
	30	321	303.75	26	28	10.00	
	31	331	313.83	26	28	10.63	
	32	341	323.92	26	28	11.35	
	33	352	334.01	26	28	12.00	
	34	362	344.11	26	28	12.80	
	35	372	354.20	26	28	13.50	
	36	382	364.29	26	28	14.40	
	37	392	374.38	26	28	15.10	
	38	402	384.48	26	28	16.00	
	39	412	394.57	26	28	16.80	
	40	422	404.67	26	28	17.70	
	41	433	414.77	26	28	18.60	
	42	443	424.86	26	28	19.50	
	43	453	434.96	26	28	20.50	
	44	463	445.06	26	28	21.45	
	45	473	455.16	26	28	22.40	
	46	483	465.25	26	28	23.40	
	48	503	485.45	26	28	25.50	
	50	524	505.65	26	28	27.70	
	52	544	525.85	26	28	29.90	
	54	564	546.05	26	28	32.30	
	60	625	606.66	26	28	39.90	
	65	675	657.17	26	28	46.80	
	70	726	707.68	26	28	54.30	
	75	777	758.20	26	28	62.30	
	80	827	808.71	26	28	70.90	
	90	928	909.75	26	28	89.58	

K 100A

SPROCKETS mm  
Tooth width (T) 17.6

CHAIN mm  
Pitch (P) 31.75  
Internal width 19.05  
Roller  $\phi$ (Dr) 19.05






PLATEWHEELS

K 120A

K 120A

SPROCKETS	mm
Teeth width (T)	23.5
CHAIN	mm
Pitch (P)	38.10
Internal width	25.40
Roller $\Phi$ (Dr)	22.23

Type	Teeth	Do	Dp	Bore d		Wt kg	Material
				Stock	Min		
K 120A	10	140	123.29	20	22	2.16	C45 Solid
	11	153	135.24	20	22	2.60	
	12	165	147.21	20	22	3.10	
	13	177	159.20	20	22	3.60	
	14	190	171.22	20	22	4.20	
	15	202	183.25	20	22	4.80	
	16	214	195.29	20	22	5.50	
	17	227	207.35	20	22	6.20	
	18	239	219.41	20	22	6.95	
	19	251	231.48	20	22	7.70	
	20	263	243.55	20	22	8.55	
	21	276	255.63	20	22	9.40	
	22	288	267.72	26	28	10.30	
	23	300	279.80	26	28	11.30	
	24	312	291.90	26	28	12.30	
	25	324	303.99	26	28	13.30	
	26	337	316.09	26	28	14.40	
	27	349	328.19	26	28	15.50	
	28	361	340.29	26	28	16.70	
	29	373	352.39	26	28	17.90	
	30	385	364.50	26	28	19.20	
	31	398	376.60	26	28	20.40	
	32	410	388.71	26	28	21.80	
	33	422	400.82	26	28	23.20	
	34	434	412.93	26	28	24.60	
	35	446	425.04	26	28	26.10	
	36	458	437.15	26	28	27.60	
	38	483	461.38	26	28	30.00	
	40	507	485.60	26	28	34.10	
	42	531	509.84	26	28	37.60	
	44	556	534.07	26	28	41.20	
	45	568	546.19	26	28	43.10	
	46	580	558.30	26	28	45.10	
	48	604	582.54	26	28	49.00	
	50	628	606.78	26	28	53.30	
	54	677	655.26	26	28	62.10	
	60	750	727.99	26	28	76.70	
	70	871	849.22	26	28	104.30	
	75	932	909.04	26	28	119.00	
	80	993	970.46	26	28	136.30	




PLATEWHEELS

K 140A  
K 160A

Type	Teeth	Do	Dp	Bore d		Wt kg	Material
				Stock	Min		
K 140A	10	163	143.84	26	28	2.90	C45 Solid
	11	178	157.78	26	28	3.60	
	12	193	171.74	26	28	4.20	
	13	207	185.74	26	28	4.90	
	14	221	199.76	26	28	5.70	
	15	236	213.79	26	28	6.60	
	16	250	227.84	26	28	7.50	
	17	264	241.91	26	28	8.40	
	18	279	255.98	26	28	9.40	
	19	293	270.06	26	28	10.50	
	20	307	284.15	26	28	11.60	
	21	322	298.24	26	28	12.80	
	22	336	312.34	26	28	14.10	
	23	350	326.44	26	28	15.30	
	24	364	340.54	26	28	16.70	
	25	379	354.65	26	28	18.10	
	26	393	368.77	26	28	19.60	
	28	421	397.00	26	28	23.80	
	30	450	425.24	26	28	28.00	
	32	478	453.49	26	28	29.70	
	35	521	495.88	26	28	35.60	
	38	563	538.27	26	28	41.90	
	40	591	565.54	26	28	46.40	
	42	620	594.81	26	28	51.10	
	45	662	637.22	26	28	58.80	
	48	705	679.63	26	28	66.90	
	50	733	707.91	26	28	72.50	
	54	790	764.47	26	28	84.60	
	60	875	849.32	26	28	104.00	

K 140A

SPROCKETS	mm
Teeth width (T)	23.5
CHAIN	mm
Pitch (P)	44.45
Internal width	25.40
Roller $\Phi$ (Dr)	25.40



Type	Teeth	Do	Dp	Bore d		Wt kg	Material
				Stock	Min		
K 160A	10	186	164.39	26	28	4.85	C45 Solid
	11	204	180.31	26	28	5.85	
	12	220	196.28	26	28	6.90	
	13	237	212.27	26	28	8.10	
	14	253	228.30	26	28	9.40	
	15	269	244.33	26	28	10.80	
	16	286	260.39	26	28	12.25	
	17	302	276.46	26	28	13.80	
	18	319	292.55	26	28	15.50	
	19	335	308.64	26	28	17.20	
	20	351	324.74	26	28	19.00	
	21	368	340.84	26	28	21.00	
	22	384	356.96	26	28	23.00	
	23	400	373.07	26	28	25.10	
	24	416	389.19	26	28	27.40	
	25	433	405.32	26	28	29.70	
	26	449	421.45	26	28	32.10	
	28	481	453.72	26	28	37.20	
	30	514	485.99	26	28	42.70	
	32	546	518.28	26	28	48.70	
	35	595	566.71	26	28	58.10	
	38	644	615.17	26	28	68.50	
	40	676	647.47	26	28	75.10	
	42	708	679.78	26	28	83.60	
	45	757	728.25	26	28	96.00	
	48	806	776.72	26	28	109.00	
	50	838	809.04	26	28	118.50	
	54	903	873.68	26	28	138.20	
	60	1000	970.65	26	28	170.00	

K 160A

SPROCKETS	mm
Teeth width (T)	29.4
CHAIN	mm
Pitch (P)	50.80
Internal width	31.75
Roller $\Phi$ (Dr)	28.58



PLATEWHEELS


K 180A  
K 200A

Type	Teeth	Do	Dp	Bore d		Wt kg	Material
				Stock	Min		
K 180A	11	229	202.85	43	45	7.8	C45 Solid
	12	248	220.81	43	45	9.3	
	13	266	238.81	43	45	10.9	
	14	285	256.83	43	45	12.6	
	15	303	274.87	43	45	14.5	
	16	322	292.94	43	45	16.5	
	17	340	311.04	43	45	18.7	
	18	358	329.11	43	45	21.5	
	19	377	347.21	43	45	23.9	
	20	395	365.33	43	45	26.6	
	21	413	383.45	63	65	28.9	
	22	432	401.57	63	65	31.7	
	24	468	437.84	63	65	37.9	
	25	487	455.99	63	65	41.2	
	26	505	474.13	63	65	44.6	
	30	578	546.74	63	65	59.6	
	35	669	637.56	63	65	81.3	
	40	760	728.41	63	65	106.4	
	45	852	819.28	63	65	134.8	
	48	903	873.81	63	65	153.5	
60	1125	1091.98	63	65	240.2		

K 180A

SPROCKETS mm  
Tooth width (T) 33.0

CHAIN mm  
Pitch (P) 57.15  
Internal width 35.72  
Roller Ø (Dr) 35.71



Type	Teeth	Do	Dp	Bore d		Wt kg	Material
				Stock	Min		
K 200A	11	254	225.39	43	45	10.4	C45 Solid
	12	275	245.34	43	45	12.3	
	13	296	265.34	43	45	14.5	
	14	316	285.37	43	45	16.8	
	15	337	305.42	43	45	19.3	
	16	357	325.49	43	45	22.5	
	17	378	345.58	43	45	25.4	
	18	398	365.68	43	45	28.5	
	19	419	385.79	63	65	31.3	
	20	439	405.92	63	65	34.7	
	21	459	426.05	63	65	38.3	
	22	480	446.20	63	65	42.1	
	24	520	486.49	63	65	50.3	
	25	541	506.65	63	65	54.6	
	26	561	526.81	63	65	59.1	
	30	642	607.49	63	65	78.9	
	35	744	708.39	63	65	107.6	
	40	845	809.34	63	65	140.7	
	45	946	910.31	63	65	178.3	
	48	1007	970.90	68	70	202.8	
60	1250	1213.31	68	70	317.3		

K 200A

SPROCKETS mm  
Tooth width (T) 35.3

CHAIN mm  
Pitch (P) 63.50  
Internal width 37.85  
Roller Ø (Dr) 69.68